



TEMPERATURE / HUMIDITY DATALOGGER		Model: <i>indi</i> 6391
Specification:		
Display	Full Icon LCD Display, 12 x 25.5mm Size	
Temp. / RH Display	Alternatively on LCD Display	
Temp. Range	-40 to 85°C (-40 ~ 185°F)	
Humidity Range	0 – 100%	
Temp. Accuracy	±0.6°C (-20 to 50°C) ±1.2°C (-40 to 20°C, 51 to 85°C)	
Humidity Accuracy	±3%Rh	
Resolution	0.1°C / 1 RH	
Sample Data	Upto 16000	
Sample Points	1k / 2k / 4k / 8k / 12k / 16k	
Sample Time	Programmable through PC	
Alarms	Hi & Lo Alarms Programmable through PC	
Alarm Indication	Provided	
Sample Indication	Provided	
On/Off	Through PC or by Magnet	
Lo Bat Indication	“LO” Displayed	
Housing	Water Resistant	
Aux. Supply	ER3 or CR2032 Lithium Battery x 1 No.	
Battery Life	6 Months Approximately	
Optional	USB PC Interface with Software Model indi 6395	

TEMPERATURE DATALOGGER		Model: <i>indi</i> 6392
Specification:		
Display	Full Icon LCD Display, 12 x 25.5mm Size	
Temp. Display	Continuously on LCD Display	
Temp. Range	-30 to 70°C (-22 ~ 158°F)	
Temp. Accuracy	±0.6°C (-20 to 50°C) ±1.2°C (-40 to 20°C, 51 to 85°C)	
Resolution	0.1°C	
Sample Data	Upto 8000	
Sample Points	1k / 2k / 4k / 8k	
Sample Time	Programmable through PC	
Alarms	Hi & Lo Alarms Programmable through PC	
Alarm Indication	Provided	
Sample Indication	Provided	
On/Off	Through PC or by Front Switch	
Housing	Water Proof	
LO Bat Indication	“bat” Flash	
Aux. Supply	CR2032	
Battery Life	6 Months Approximately	
Optional	USB PC Interface with Software Model indi 6395	

USB PC INTERFACE FOR DATALOGGER	Model: <i>indi</i> 6395
	

<p>Source 1 INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p>Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p>Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com</p> <p>Branch Offices: Raikot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p>3 YEAR*</p> <p>REPLACEMENT</p> <p>WARRANTY</p>
---	--