




<b>PORTABLE THERMOMETER WITH SENSOR</b>		Model: <i>indi</i> 6321
<b>Specification:</b>		
Display	1999 Count LCD	
Range	-50 to 1300°C	
Resolution	1°	
Accuracy	±0.5% of Full Scale	
Sensor	Suitable for Cr/Al ('k') type sensor	
Battery	9V Battery	
Sensor Type	Handle type Cr/Al sensor Leaf or Needle	
Enclosure	Portable (Hand Held) type	
Power On/Off	Switch Provided	
Carrying Case	Provided	

<b>PORTABLE THERMOMETER WITH SENSOR</b>		Model: <i>indi</i> 6322
<b>Specification:</b>		
Display	3999 Count Full Icon LCD	
Range	-50 to 300.0°C (-58 to 572°F)	
Resolution	0.1°	
Accuracy	±1°	
Sensor	Built in with indicator	
Battery	1.5V Battery	
Memory	Max. / Min	
Alarm	Hi / Lo Provided	
Table Stand	Provided	
Enclosure	Portable (Hand Held) type	

<b>FLAMEPROOF INDICATOR / CONTROLLER</b>		Model: <i>indi</i> 6346
<b>Specification:</b>		
Display	1999 Count LED	
Range	As Required	
Input	Pt-100 RTD, 'J'/'K' Thermocouple, 4-20mADC/0-10VDC/0-20mADC Analogue Input	
No. of Inputs	1, 6 or 12	
Resolution	0.1 / 1	
Accuracy	±0.5% of Full Scale	
Set Point	1 or 2 (Controller Only)	
Battery	9V Battery	
Output	Relay / SSR (Controller Only)	
Enclosure	CMRI Dhanbad Certified for Gas Group IIA & IIB	
Supply	230±10%VAC	

<h2 style="color: red;">Source 1</h2> <p>INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p>Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p>Email: <a href="mailto:sales@source1in.com">sales@source1in.com</a> <a href="mailto:source1in@indiatimes.com">source1in@indiatimes.com</a> URL: <a href="http://www.source1in.com">www.source1in.com</a></p> <p>Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p><b>3 YEAR*</b></p> <p><b>REPLACEMENT</b></p> <p><b>WARRANTY</b></p>
---	--