




<b>DIGITAL PRESSURE CUM VACUUM GAUGE (MANOMETER)</b>		Model: <i>indi</i> 6361
<b>Specification:</b>		
Display of	Pressure or Differential Pressure	
Display	Full Icon LCD	
Pressure Range	0-5psi or 0-15psi or 0-30psi or 0-100psi	
Max. Pressure Range	0-20psi or 0-30psi or 0-60psi or 0-150psi	
Repeatability	±0.2% (±0.5% Max.)	
Accuracy	±0.3% of Full Scale at +25°C	
Response Time	0.3 Seconds	
Combined linearity and hysteresis	±0.29(Max ±1.0)%FSO	
Unit Selection	bar, mbar, psi, kPa, inHg, mmHg, ozin <sup>2</sup> , inH <sub>2</sub> O, ftH <sub>2</sub> O, kgcm <sup>2</sup>	
Special Functions	Data Hold, Backlight, Auto Power Off	
Battery	9V Battery	
Memory Recall	Max. /Min.	
RS232 Output	Provided (Software & Cable Optional)	
Serial Format	Baud rate 2400 Baud, 1 Stop bit, 8 Data bits. PXXX.XX	
Cabinet Size	72 x 182 x 30 mm	
Carrying Case	Provided	

<b>DIGITAL PRESSURE CUM VACUUM GAUGE (MANOMETER) (High Resolution)</b>		Model: <i>indi</i> 6362
<b>Specification:</b>		
Display of	Pressure or Differential Pressure	
Display	Full Icon LCD	
Pressure Range (Resolution)	0 - 2psi (0.004), 0-±138mbar (0.1), 0-±55.4 inH <sub>2</sub> O (0.01), 0-±1410mmH <sub>2</sub> O (1), 0-±0.138bar (0.001),	
Max. Pressure Range	0 - 20psi	
Repeatability	±0.2% (±0.5% Max.)	
Accuracy	±0.3% of Full Scale at +25°C	
Response Time	0.3 Seconds	
Combined linearity and hysteresis	±0.29(Max ±1.0)%FSO	
Unit Selection	bar, mbar, psi, mmH <sub>2</sub> O, inH <sub>2</sub> O	
Special Functions	Data Hold, Backlight, Auto Power Off	
Battery	9V Battery	
Memory Recall	Max. /Min.	
RS232 Output	Provided (Software & Cable Optional)	
Serial Format	Baud rate 2400 Baud, 1 Stop bit, 8 Data bits. PXXX.XX	
Cabinet Size	72 x 182 x 30 mm	
Carrying Case	Provided	

<b>DIGITAL PRESSURE GAUGE (MANOMETER)</b>		Model: <i>indi</i> 6364
<b>Specification:</b>		
DISPLAY	3 ½ / 4 ½ Digit L.C.D	
Range	As Required	
RESOLUTION	0.1 / 0.01	
ACCURACY	+/- 0.25%	
UNIT SELECTION	As required	
POWER SUPPLY	9 Volts D.C. Battery / 230 V.A.C. Power Adaptor / 24VDC	
SENSOR	Built In Imported Stainless Steel Sensor with S.S. 316 Wetted Parts	
CONNECTION	Standard 3/8" S.S. Threaded End Connection or as required	
ENCLOSURE	IP 66 Enclosure (weather proof) ABS	
SIZE	120 x 80 x 85 mm. (L x B x H)	

<h2 style="color: red;">Source 1</h2> <p>INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p>Tel: (0260) 325 1066    Fax: (0260) 2401654    Mob: 93770 29027 / 98244 64050</p> <p>Email: <a href="mailto:sales@source1in.com">sales@source1in.com</a>    <a href="mailto:source1in@indiatimes.com">source1in@indiatimes.com</a>    URL: <a href="http://www.source1in.com">www.source1in.com</a></p> <p>Branch Offices: Rajkot   Baroda   Surat   Ahmedabad   Chandigarh   Nashik   Pune   Coimbatore</p>	<p><b>1 YEAR</b></p> <p><b>REPLACEMENT</b></p> <p><b>WARRANTY</b></p>
---	---