






THERMO-HYGROMETER WITH CLOCK		Model: <i>indi</i> 6331
Specification:		
Display	Two Line Full Icon LCD Display with Calendar	
Temp. Range	-5 – 50°C (23 – 122°F)	
Accuracy	0.1°C (1.8°F)	
Resolution	0.1°C (0.2°F)	
Humidity Range	30% RH-90%RH	
Hour & Daily Alarm	Provided	
Selection	12/24 Hour, °C / °F	
Special Function	Max./Min. Temp. & Humidity Display	
Aux. Supply:	2 x 1.5V AAA Size Battery	
Cabinet Size	110 X 69 X 20 mm, Wall Hanging or Table Top	

THERMO-HYGROMETER WITH CLOCK		Model: <i>indi</i> 6333
Specification:		
Display	2 Line Full Icon LCD Large Display	
Temp. Range	-50 – 70°C	
Accuracy	0.1°C	
Resolution	0.1°C / 1% RH	
Humidity Range	10% RH-99%RH	
Memory	High / Low Temp. & Humidity	
Operation	3 Button for Max/Min, Reset, Hour & Minute	
Aux. Supply:	1 x 1.5V AAA Size Battery	
Cabinet Size	161 X 69 X 32mm, Wall Hanging & Table top	

THERMO-HYGROMETER (Portable)		Model: <i>indi</i> 6335
Specification:		
Display	Dual Back light LCD Display for Temp. & Humidity	
Range	0 - +40°C / 0 - 100% (Air Probe), -20 to 1000°C ('K' T/C)	
Accuracy	Temp. ±3% / Humidity: ±3.5%,	
Resolution	Temp.: 0.1 / 1°C / Humidity: 0.1%	
Function	°C / °F Switchable, MAX and Hold function	
Sensor	Wired Sensor	
Aux. Supply	9V Battery (10 Minute Auto Power Off)	
Cabinet Size	150mm x 72mm x 35mm	
Accessories	K-type temperature probe, Humidity Probe, Soft Carrying Bag	

THERMO-HYGROMETER (With Separate Probe)		Model: <i>indi</i> 6334
Specification:		
Display	Dual LCD Display for Temp. & Humidity	
Range	0 - +50°C / 20 - 99%	
Accuracy	Temp. ±1°C / Humidity: ±3%,	
Resolution	Temp.: 0.1°C / Humidity: 1%	
Sensor Type	Temp.: Thermistor / Humidity: High-molecular resistance	
Sensitivity	10 Sec Update	
Oper. Temp.	-10 ~ +50°C	
Sensor Wire	1 Meter long Sensor Wire	
Aux. Supply	1 x 1.5V AA Size Battery	
Cabinet Size	70 (W) x 33 (H) x 22 (D) mm	
Panel Cutout Size	66.1 x 29.5	

TEMP. / HUMIDITY INDICATOR		Model: <i>indi</i> 6397
Specification:		
Temp. Range	0 – 65°C	
Accuracy	±0.6°C	
Humidity Range	5% - 95% RH	
Accuracy	±3%	
Display	3 ½ Digit Dual LCD, 12.5mm H	
Oper. Supply	24VDC or 230VAC	
Optional Output	4-20mADC Output	
Oper. Temp.	0 – 65°C	
Oper. Humidity	5% - 95% RH	
Enclosure Type	IP 66 Enclosure (weather proof) ABS	
Enclosure Size	120 x 80 x 85 mm. (L x B x H)	
Option	Built in Sensor or Wired Sensor	

Source 1 INSTRUMENTS

Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.
 Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050
 Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com
 Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore

3 YEAR*
REPLACEMENT
WARRANTY