






INFRARED THERMOMETER		Model: <i>indi</i> 6306
Specification:		
Display	Full Icon LCD	
Temp. Range	-22°C – 120°C (-7°F – 248°F)	
Accuracy	2% of reading or ±2°C whichever is greater	
Resolution	0.1°C/F	
Emissivity	0.95 Fixed	
Switch Selection	°C / °F, Min./ Max. Function, Auto Scan, Auto Power Off	
Field of View	1:1.3	
Data Hold	Provided	
Response Time	<0.5 Seconds	
Aux. Supply	Battery	
Dimension / Weight	40 x 70mm	


INFRARED THERMOMETER		Model: <i>indi</i> 6310
Specification:		
Display	Full Icon LCD	
Temp. Range	-30 to 450°C (-22 to 842°F)	
Accuracy	±2% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1 (<200°C) / 1 (>200°C)	
Emissivity	0.95 Fixed (Covers 90% of Application)	
Spectral Response	6 ~ 14um	
Switch Selection	Provided for Backlight On/Off, °C/°F and Infrared	
Field of View	8:1 (at 8" Distance measures 1" Target)	
Aux. Supply:	9V Battery (Auto Power Off After 7 Seconds)	
Accessories	Carrying Bag	
Dimension / Weight	159 x 79 x 57.2mm / 190gms	


INFRARED THERMOMETER		Model: <i>indi</i> 6311
Specification:		
Display	Full Icon LCD	
Temp. Range	-50 to 600°C (-58 to 1112°F)	
Accuracy	±2% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1 (<200°C) / 1 (>200°C)	
Emissivity	0.95 Fixed (Covers 90% of Application)	
Spectral Response	6 ~ 14um	
Switch Selection	Provided for Backlight On/Off, °C/°F and Infrared	
Field of View	8:1 (at 8" Distance measures 1" Target)	
Aux. Supply:	9V Battery (Auto Power Off After 7 Seconds)	
Accessories	Carrying Bag	
Dimension / Weight	159 x 79 x 57.2mm / 190gms	


INFRARED THERMOMETER		Model: <i>indi</i> 6312
Specification:		
Display	Full Icon LCD	
Temp. Range	-20 to 1000°C (-50 to 1832°F)	
Accuracy	±1.5% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1 / 1	
Emissivity	0.95 Fixed (Covers 90% of Application)	
Switch Selection	Provided for Backlight On/Off, °C/°F and Infrared, Data Hold	
Field of View	50:1 (at 50" Distance measures 1" Target)	
Range Selection	Automatic	
Aux. Supply:	9V Battery	
Accessories	Carrying Bag	
Dimension / Weight	159 x 79 x 57.2mm / 190gms	

<h2 style="color: red;">Source 1</h2> <p>INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p>Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p>Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com</p> <p>Branch Offices: Rajkot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p style="color: blue; font-weight: bold;">1 YEAR</p> <p style="color: red; font-weight: bold;">REPLACEMENT WARRANTY</p>
---	--

INFRARED THERMOMETER (Adjustable Emissivity)		Model: <i>indi</i> 6313
Specification:		
Display	Full Icon LCD Backlight	
Temp. Range	-50 to 750°C (-32 to 1382°F)	
Accuracy	±1.5% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1	
Emissivity	Adjustable from 0.1 to 1.0	
Switch Selection	Provided for Backlight On/Off, °C/°F and Infrared, Data Hold	
Field of View	16:1 (at 50" Distance measures 1" Target)	
Special Functions	Max., Min., Dif., Avg., Trigger Lock, Lo / Hi Alarms	
Aux. Supply:	9V Battery	
Accessories	Hard Carrying Bag	
Dimension / Weight	159 x 79 x 57.2mm / 190gms	

INFRARED THERMOMETER (Adjustable Emissivity)		Model: <i>indi</i> 6314
Specification:		
Display	Full Icon LCD	
Temp. Range	-20 to 500°C (-4 to 932°F)	
Accuracy	±2% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1°C / 0.2°F	
Emissivity	0.1 to 1.0 Adjustable (1326: Fixed 0.95)	
Switch Selection	Provided for Backlight On/Off, °C/°F and Infrared	
Field of View	8:1 (at 8" Distance measures 1" Target)	
Function / Memory	Max./Min., Read Function, Data Memory (99 Sets)	
Aux. Supply:	9V Battery (Auto Power Off)	
Accessories	Carrying Bag	
Dimension / Weight	170 x 118 x 46 mm / 200gms	

2 in 1 INFRARED THERMOMETER (Adjustable Emissivity)		Model: <i>indi</i> 6315
Specification:		
Display	Full Icon LCD	
Temp. Range	-60 to 500°C (-4 to 932°F) for Infrared, -20 to 1400°C (-83.2 to 1999°F) for 'k' Thermocouple	
Accuracy	±2% of Reading or ±2°C/±4°F (Whichever is greater)	
Resolution	0.1 / 1	
Emissivity	0.1 to 1.0 Adjustable (1326: Fixed 0.95)	
Mode	Ave., Diff., Hi/Lo Alarm, Max./Min./Lock, Backlight, Buzzer,	
Field of View	8:1 (at 8" Distance measures 1" Target)	
Range Selection	Automatic	
Aux. Supply:	1.5V x 2 AA Size Battery (Auto Power Off)	
Accessories	Carrying Bag	

2 in 1 INFRARED THERMOMETER (Adjustable Emissivity)		Model: <i>indi</i> 6316
Specification:		
Display	Full Icon LCD	
Temp. Range	-18 to 1000°C (0 to 1832°F) for Infrared, -40 to 1200°C (-40 to 2192°F) for 'k' Thermocouple	
Accuracy	±2% of Reading or ±3.5°C/±4°F (Whichever is greater)	
Resolution	0.1 / 1	
Emissivity	0.3 to 0.99 Adjustable (1326: Fixed 0.95)	
Mode	Ave., Diff., Hi/Lo Alarm, Max./Min./Lock, Backlight, Record,	
Field of View	8:1 (at 8" Distance measures 1" Target)	
Range Selection	Automatic	
Aux. Supply:	9V Battery (Auto Power Off)	
Accessories	Carrying Bag	

<h1 style="color: red;">Source 1</h1> <p>INSTRUMENTS</p> <p>Plot No. L/715/10, 40 Shed Area, GIDC, Vapi – 396195. Gujarat. India.</p> <p>Tel: (0260) 325 1066 Fax: (0260) 2401654 Mob: 93770 29027 / 98244 64050</p> <p>Email: sales@source1in.com source1in@indiatimes.com URL: www.source1in.com</p> <p>Branch Offices: Raikot Baroda Surat Ahmedabad Chandigarh Nashik Pune Coimbatore</p>	<p style="color: red; font-weight: bold; font-size: 1.2em;">1 YEAR REPLACEMENT WARRANTY</p>
---	---